

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representation of  
The original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 0 793 019 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
03.09.1997 Bulletin 1997/36

(51) Int Cl.<sup>6</sup>: F04B 25/02, F04B 35/04

(21) Application number: 97301303.0

(22) Date of filing: 27.02.1997

(84) Designated Contracting States:  
CH DE FR GB LI

• Schofield, Nigel Paul  
Horsham, West Sussex RH13 5SJ (GB)

(30) Priority: 01.03.1996 GB 9604645

(74) Representative: Bousfield, Roger James et al  
The BOC Group plc  
Chertsey Road  
Windlesham Surrey GU20 6HJ (GB)


(71) Applicant: The BOC Group plc  
Windlesham Surrey GU20 6HJ (GB)

(72) Inventors:  
• Stones, Ian  
Crawley, West Sussex RH10 7FZ (GB)

### (54) Improvements in vacuum pumps.

(57) A vacuum pump which comprises a multi-stage reciprocating piston mode of operation in which piston reciprocation is effected by electromagnetic drive means and a counter-acting spring means and in which

the pump stages are connected in series between a pump inlet and a pump outlet such that, in use, gas being transferred through the pump passes through the stages in turn.



EP 0 793 019 A2

## Description

This invention relates to improvements in vacuum pumps and, more particularly, to such pumps incorporating a reciprocating piston.

There is a general need for small, dry (ie oil-free in operation) vacuum pumps for use in a variety of scientific and analytical purposes and for use in the backing of other vacuum pumps including turbo-molecular pumps in particular.

Current pumps include diaphragm pumps, but these have a limited diaphragm life expectancy (typically 6000 hours).

Vacuum pumps incorporating a reciprocating piston mode of operation are known which have an electromagnetic actuator comprising a wound coil and an iron core arrangement and a piston with a magnetic member at one end positioned within the electromagnet. Repeated magnetisation and de-magnetisation of the electromagnet by passing half wave rectified pulses of alternating current or pulsed direct current through the coil causes the magnetic member fixed to the piston arrangement to move within the cylindrical coil and causes fluid to be sucked in to a cylinder and then be exhausted therefrom at each piston cycle aided by the use of one-way valves in a manner known *per se*.

Such pumps have, however, not been generally applied to low pressure applications, for example below 100 mbar absolute, due to their general relative lack of overall vacuum performance.

The present invention is concerned with the provision of an electromagnetically actuated piston based vacuum pump which generally affords the possibility of such greater efficiencies and improved vacuum performance.

In accordance with the invention, there is provided a vacuum pump which comprises a multi-stage reciprocating piston mode of operation in which piston reciprocation is effected by electromagnetic drive means and a counter-acting spring means and in which the pump stages are connected in series between a pump inlet and a pump outlet such that, in use, gas being transferred through the pump passes through the stages in turn.

The term "multi-stage" used herein means a minimum of two stages. Preferably, however, pumps of the invention possess three or four or more stages in series.

Preferably also, the pump possesses one or more double acting piston heads with each such piston head defining two pump stages, ie one on either side of the piston head, within the cylinder with which it is associated. A pump with four stages comprising two double acting pistons is most preferred.

In preferred embodiments of the invention, the pump possesses one or two or more of such double acting piston heads contained within the same cylinder block. Advantageously, all such piston are present on the same piston shaft.

The preferred form of electromagnetic drive means is a solenoid actuator operating on half wave rectified AC current or pulsed direct current which during the magnetisation period with current flowing through the coils of the solenoid drives a magnetic plunger to which the piston is attached to bridge an air gap in an iron core surrounding the coils.

The general features of the invention are particularly suited to preferred embodiments in which all the pump stages are present on one side of the pump drive means.

In such preferred embodiments and generally, it is advantageous for one or both of:

- the pump piston heads all to be present on the same piston shaft and for the piston shaft to be positioned for reciprocation along the main axis of the pump, and
- the pump piston shaft to pass centrally through the electromagnetic drive means.

The above advantageous features allow for the possibility of a bearing to be mounted on the plunger arrangement utilising the internal surfaces of the iron core pole pieces of the solenoid as bearing surfaces during reciprocation of the plunger and an attached piston shaft, thereby ensuring concentricity between the plunger and the iron core pole pieces. Such advantageous features also afford the possibility of cooling the solenoid from the outside, ie from outside the vacuum envelope of the pump, leading to a potential longer life for the solenoid and the pump as a whole.

Each stage of the pumps of the invention require in general one way valves to allow, at relevant positions of the piston head within its cylinder, gas to enter the stage from the pump inlet or previous stage and also to allow gas to be exhausted from that stage and to pass in to the subsequent stage or the pump outlet.

In preferred embodiments in which all the pump stages are situated on one side of the pump drive means, it has been found to be advantageous for all such valves to be present in a single valve plate attached to an external surface of the cylinder block and which can be removed for easy maintenance.

Preferably such a single valve plate is positioned intermediate the cylinder block and a manifold in which are defined a pump inlet, outlet, and the various passageways and parts required to link each pump stage in series via the valves of the valve plate.

An important feature of the invention is the spring means used in the pump to counter-act the drive means in those parts of the electromagnetic cycle when the coils are not magnetised. The use of such a spring means is essential for obvious reasons.

However, in addition to such a counter-acting spring means, it has also been found to be advantageous to employ a further spring means acting in the same direction as the electromagnetic drive means to counteract

the forces generated by the pressure differentials across the piston faces at lower inlet pressures, thereby balancing the piston arrangement in a relatively central stroke position.

In the case of a solenoid actuator of the type described above in particular, it has been found that the use of such counter-acting spring means can act, in conjunction with the solenoid drive means, to effect a resonant system. In such a system, it is clear that the force exerted by the two spring means on the plunger/piston must be carefully chosen but this is readily achievable by those skilled in the art.

Good inter-stage vacuum seals within the pump and, in particular, on the piston shaft are essential to good performance of the pump. A plurality of seals of known design can usefully be employed along the length of the shaft/head, for example contained in grooves around the peripheries of the shaft/head component(s).

For a better understanding of the invention, reference will now be made, by way of exemplification only, to the accompanying drawings in which:

Figure 1 is a schematic perspective view of a pump of the invention, partly exploded to show a valve plate and a manifold thereof more clearly, and

Figure 2 is a schematic sectional view through the pump of Figure 1 along the line II-II of Figure 1 but with the valve plate and the manifold in position.

With reference to the drawings there is shown a piston pump 1 of the invention having as an integral part thereof a solenoid drive means 2.

A substantially square cross-section body member 3 has defined therein two circular diameter bores 4, 5 linked by a further circular bore 6. The bore 5 of the body member 3 is sealed by the circular end plate 7 by means in particular of circumferential seal 8.

The other end of the body member 3 is sealed to a first iron core pole piece 9 of the solenoid drive means 2 by means of a further circumferential seal 10.

A further iron core pole piece 11 of the same generally circular cross sectional size as the piece 9 is present which define an air gap 12 therebetween.

A wound coil 13, supported and electrically insulated by a plastic bobbin 14, is enveloped by the iron core, comprising the aforementioned iron core pole pieces 9, 11 and laminated iron cage 15, thereby completing, with a plunger described below, the solenoid drive means 2.

The pump being sealed from atmosphere at the solenoid end by means of circumferential sealing 'N' between the plastic bobbin 14 and core pole pieces 9, 11, providing an overall hermetically sealed unit from inlet to exhaust, suitable for handling toxic process gases.

The solenoid plunger 16 is of hollow cylindrical shape and is sized externally to fit closely the internal

cylindrical surface of the core pole pieces 9, 11 and therefore is adapted to reciprocate axially therein. A solenoid bearing 'X' mounted on the same means as the plunger 16 provides concentricity between the plunger and pole pieces 9, 11. To maintain the running surface quality for the bearing X, and to avoid corrosion of the iron components, the surfaces of the core pole pieces 9, 11 and plunger 16 are advantageously coated with a suitable coating, for example Hard Chrome.

The plunger 16 is attached to a plunger carrier 17 which is itself securely fitted by means of a bolt 18 to a piston shaft 19.

The piston shaft 19 extends through a circular bore 20 in the pole piece 9 and is sealingly adapted for axial reciprocation therein by means of a series of shaft seals 21 contained in a plurality of circumferential grooves in the external surface of the shaft 19.

The piston shaft 19 further extends through the circular bore 6 in the body member 3 and is again sealingly adapted for axial reciprocation therein by means of a further series of shaft seals 22 contained in a plurality of circumferential grooves in the external surface of the shaft 19.

The piston shaft 19 has integrally formed therewith a double acting piston head 23 having a cylindrical outer portion which is sealingly adapted for reciprocation within the bore 4 of the body member 3. A central bearing 24(b) and an outer seal arrangement 24(a) is contained in a plurality of circumferential grooves in the external surface of this cylindrical outer portion of the piston head 23.

The piston shaft also has attached thereto by means of a bolt 25 a further piston head 26 which also has a cylindrical outer portion which is sealingly adapted for reciprocation within the bore 5 of the body member 3. A series of seals 26(b) are contained in three circumferential grooves in the external surface of this cylindrical outer portion of the piston head 26.

The piston head 23 therefore defines the first two stages of the pump, one being to the left (as shown) of the piston head 23 and the second being to the right (as shown) of the piston head 23.

The piston head 26 defines the third and fourth stages of the pump, the third being to the left (as shown) of the piston head 26 and the fourth being to the right (as shown) of the piston head 26.

In Figure 1, the piston arrangement is shown in a position to the left, so that the volumes associated with the second and fourth stages being "open" and the volumes associated with the first and third stages being "closed".

The body member 3 can therefore be regarded as a single cylinder block of the pump sealed at one end by the end plate 7 and at the other end by the pole piece 9.

The pump has an inlet 27 and an outlet 28 between which are provided passageways for gas drawn in to the inlet 27 to pass through the four stages in series and

sequentially before being exhausted through the outlet 28.

In accordance with preferred embodiments of the invention, the inlet 27 and outlet 28 are formed in to a manifold 29 which also provides the necessary passageways for transmission of the gas through the four stages of the pump in conjunction with a single valve plate 30 sandwiched between the body portion 3 and the manifold 29 in which one way valves are present to allow entry in to and exhaust from each chamber is allowed at relevant times during the piston cycle. The use of such a manifold and valve plate allows for a more simple construction of the pump and more ready maintenance thereafter.

Associated with the plunger carrier 17 are two coil springs 31 and 32. The spring 31 is required to exert a force on the plunger carrier 17, and hence on the piston arrangement 19 as a whole, to urge it back to the position shown in Figure 1 where no current is passing through the coil 13, ie when the electromagnetic actuator is inactive. At lower pressures, this force is complemented by pressure differential forces acting on the piston-faces in the same direction. In that part of the cycle when the actuator is active, the movement of the plunger to bridge the gap 12 in the pole pieces 9,11 exerts a compressive force on the spring 31.

The spring 32 acts in a direction to complement the electromagnetic force of the solenoid drive 2. Optimisation of the balancing of the dynamic forces exerted by this spring on the plunger carrier 17, coupled with the magnetic force acting on the plunger 16, relative to that exerted in the opposite direction by the spring 31 and pressure differential forces results in the provision of a drive mechanism system which is resonant and provides preferably stroke characteristics. Such a resonant system is aided by use of the features, particularly the preferred embodiments, of the invention.

In use of the pumps of the invention, the application to the electromagnetic drive means, preferably the solenoid actuator, of a half wave rectified AC pulsed current during a half cycle of the piston and aided in particular by the force exerted by the spring 32 and utilising the force exerted by the spring 31 in the opposite direction during the other half cycle of the piston affords the opportunity of the setting up of a resonant action for the piston and for the pump as a whole which leads to enhanced pump efficiency.

Spring adjustment means for either or both of the springs 31, 32 although not shown in the drawings may be incorporated to enable the force(s) extended by the springs to be adjusted in situ.

means and a counter-acting spring means and in which the pump stages are connected in series between a pump inlet and a pump outlet such that, in use, gas being transferred through the pump passes through the stages in turn.

2. A pump according to Claim 1 having at least three stages in series.
3. A pump according to Claim 1 or Claim 2 which possesses one or more double acting piston heads with each such piston head defining two pump stages within the cylinder with which it is associated.
4. A pump according to any preceding claim in which all the pump stages are present on one side of the pump drive means.
5. A pump according to any preceding claim in which the pump piston heads are all present on the same piston shaft and the piston shaft is positioned for reciprocation along the main axis of the pump.
6. A pump according to any preceding claim in which the pump piston shaft passes centrally through the electromagnetic drive means.
7. A pump according to any preceding claim having a single valve plate in which one way valves are present to allow entry in to and exhaust from each stage at relevant times of the piston cycle.
8. A pump according to any preceding claim in which a first spring means complements the electromagnetic force of the drive means and a second spring means acts in the opposite direction on the drive means to provide a resonant system.

## Claims

1. A vacuum pump which comprises a multi-stage reciprocating piston mode of operation in which piston reciprocation is effected by electromagnetic drive





FIGURE 1

**THIS PAGE BLANK (USPTO)**



**THIS PAGE BLANK (USPTO)**

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 0 793 019 A3

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
02.06.1999 Bulletin 1999/22

(51) Int Cl.<sup>6</sup>: F04B 25/02, F04B 35/04

(43) Date of publication A2:  
03.09.1997 Bulletin 1997/36

(21) Application number: 97301303.0

(22) Date of filing: 27.02.1997

(84) Designated Contracting States:  
CH DE FR GB LI

• Schofield, Nigel Paul  
Horsham, West Sussex RH13 5SJ (GB)

(30) Priority: 01.03.1996 GB 9604645

(74) Representative: Bousfield, Roger James et al  
The BOC Group plc  
Chertsey Road  
Windlesham Surrey GU20 6HJ (GB)


(71) Applicant: The BOC Group plc  
Windlesham Surrey GU20 6HJ (GB)

(72) Inventors:  
• Stones, Ian  
Crawley, West Sussex RH10 7FZ (GB)

### (54) Improvements in vacuum pumps

(57) A vacuum pump which comprises a multi-stage reciprocating piston mode of operation in which piston reciprocation is effected by electromagnetic drive means and a counter-acting spring means and in which

the pump stages are connected in series between a pump inlet and a pump outlet such that, in use, gas being transferred through the pump passes through the stages in turn.



EP 0 793 019 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 30 1303

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 93 01411 A (CHEN CHONGYUAN) 21 January 1993 * abstract; figures 10,11 *	1,2	F04B25/02 F04B35/04
Y	PATENT ABSTRACTS OF JAPAN vol. 013, no. 194 (M-823), 10 May 1989 & JP 01 019189 A (NAGANO KEIKI SEISAKUSHO:KK), 23 January 1989 * abstract *	1,2,4-6	
Y	US 4 954 047 A (OKUYAMA NOBUHISA ET AL) 4 September 1990 * column 6, line 46 - column 7, line 43; figure 3 *	1,2,4-6	
A	FR 2 666 853 A (TOYO ENGINEERING CORP) 20 March 1992 * page 9, line 32 - page 17, line 147; figures 1-7 *	1	
A	GB 2 040 361 A (PIERBURG GMBH & CO KG) 28 August 1980 * the whole document *	3	TECHNICAL FIELDS SEARCHED (Int.Cl.6) F04B
A	US 4 699 572 A (BEZ ECKHARD ET AL) 13 October 1987 * abstract; figure 1 *	1	
A	DE 27 15 102 A (SYNDICAT DES COPROPRIETAIRES D) 12 October 1978 * page 6, paragraph 2 - page 8, paragraph 1; figure 1 *	1	
A	US 4 832 578 A (PUTT JAMES C) 23 May 1989 * abstract; figures 2,3 *	1	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>8 Apr11 1999</b>	Examiner <b>Ingelbrecht, P</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P/C/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 30 1303

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-04-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9301411 A	21-01-1993	JP 5018351 A	26-01-1993
US 4954047 A	04-09-1990	JP 2102385 A	13-04-1990
		CA 2000152 A,C	08-04-1990
		FR 2637654 A	13-04-1990
FR 2666853 A	20-03-1992	JP 4128578 A	30-04-1992
GB 2040361 A	28-08-1980	DE 2855608 A	26-06-1980
		FR 2445903 A	01-08-1980
		JP 55123384 A	22-09-1980
		SE 7910423 A	23-06-1980
US 4699572 A	13-10-1987	AT 38542 T	15-11-1988
		WO 8300539 A	17-02-1983
		AU 564301 B	06-08-1987
		DE 3279209 A	15-12-1988
		EP 0085687 A	17-08-1983
		JP 4072073 B	17-11-1992
		JP 58501474 T	01-09-1983
		US 4790726 A	13-12-1988
DE 2715102 A	12-10-1978	NONE	
US 4832578 A	23-05-1989	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82